UbeCube

4429 E 139th St
Grandview, MO 64030
816.775.2044

ATTACHMENTS + ACCESSORIES - INSTALLATION GUIDE

Drill Holder



CrateHook™



Cup Holder



Plier Holder



Short Pole



Tool Hook





Handle Kit





Fishing Pole Holder

IMPORTANT USE NOTES

Check Compatibilty: The Handle Kit is designed for the UC01 Mod and UC02 Mod crates only. It is not compatible with the UC02 crates.


Handle Kit Carry Limit: Do not carry a crate by the Handle Kit if the loaded crate weighs more than 50 lbs. Excess weight may cause the handle to slip off the handle anchors.

Check Before Use: Make sure each attachment is fully locked onto the crate before loading or carrying the crate.

Inside Or Outside Mounting: All 1/4 Turn Attachments can be installed on the inside or outside of the crate.

Fishing Pole Holder Placement: The Fishing Pole Holder is designed for outside-of-crate installation only.

TOOLS REQUIRED FOR ASSEMBLY



Flat Head Screwdriver

Used for the Handle Kit assembly.

ATTACHMENT INSTALL

1/4 Turn Attachments







1 — 2

Insert the 1/4 Turn Attachment into the grid openings **at a 45-degree angle.**

Rotate the Attachment 45 degrees until it locks securely onto the crate panel.

Fishing Pole Holder





1 — 2


Insert the Fishing Pole Holder into a grid opening **on the outside of the crate.**

From inside the crate, insert and rotate the D-Ring Connector 45 degrees to lock the Fishing Pole Holder in place.


Visit us @ ubecube.com to learn more!!

HANDLE KIT ASSEMBLY


Unlock Panel




Remove Panel



Remove Pin Locks



Re-Secure Panel



1 — 2 — 3 — 4


Rotate **all four of the Pin Locks 90 degrees clockwise** to unlock the grid panel.

Remove the panel by **pushing inward on each of its four corners** from the outside of the crate.


Rotate two Pin Locks 90 degrees, then **press the pin button with a flathead screwdriver while pulling the pin out** of the casing.

Insert the Grid Panel back into the crate and **rotate the lower two Pin Locks** to lock the Grid Panel in place.


Assemble Handle



Handle To Panel



Tighten Bolt



Repeat 6 & 7



5 — 6 — 7 — 8

Press the rubber handle opening over the metal anchor cylinder until it wraps fully around the anchor.

Insert the back side of the Rubber Handle assembly **into the empty Pin Lock cavity.**

From inside the crate, insert the bolt and tighten it into the Handle assembly with a flathead screwdriver.

Repeat steps 6 & 7 for the other side of the handle until both sides are secure.